

### 气源处理件



工作介质：空气      最高使用压力：1.0MPa      滤芯精度：40μm

调压范围：0.05~0.9MPa      保证温度范围：-20℃~70℃

GC200/300/400/600		型号	A	B	C	D	E	F	G	H	I	J	K
	GC200-06	62	30	25	PT1/8		147	93	5.5	50	8.5	133	
	GC300-08	72	41.5	35	PT1/4	G1/8	188	143	6.5	64	9	188	
	GC300-10	72	41.5	35	PT3/8	G1/8	188	143	6.5	64	9	188	
	GC300-15	72	41.5	35	PT1/2	G1/8	188	143	6.5	64	9	188	
	GC400-10	89	50	40	PT3/8	G1/4	248	166.5	8.6	84	12	216	
	GC400-15	89	50	40	PT1/2	G1/4	248	166.5	8.6	84	12	216	
	GC600-20	118	70	50	PT3/4		309	219	11	105	16	282	

GFC200/300/400/600		型号	A	B	C	D	E	F	G	H	I	J	K
	GFC200-06	62	30	50	PT1/8		M30×1.5	97	93	5.5	9	161	
	GFC300-08	72	41.5	70	PT1/4	G1/8	M40×1.5	124	143	6.5	9	225.5	
	GFC300-10	72	41.5	70	PT3/8	G1/8	M40×1.5	124	143	6.5	9	225.5	
	GFC300-15	72	41.5	70	PT1/2	G1/8	M40×1.5	124	143	6.5	9	225.5	
	GFC400-10	89	50	80	PT3/8	G1/4	M55×2.0	164	167	8.6	12	270.5	
	GFC400-15	89	50	80	PT1/2	G1/4	M55×2.0	164	167	8.6	12	270.5	
	GFC600-20	118	70	100	PT3/4		M68×1.5	204	219	11	16	363	

GFR200/300/400/600		型号	A	B	C	D	E	F	G	H	I	J	K
	CFR200-06	30	32	M30×1.5	PT1/8		55	34	28	93	48	161	
	CFR300-08	41	31	M40×1.5	PT1/4	G1/8	53	40	38	143	46	225.5	
	CFR300-10	41	31	M40×1.5	PT3/8	G1/8	53	40	38	143	46	225.5	
	CFR300-15	41	31	M40×1.5	PT1/2	G1/8	53	40	38	143	46	225.5	
	CFR400-10	50	40	M55×2.0	PT3/8	G1/4	72	52	52	167	53	270.5	
	CFR400-15	50	40	M55×2.0	PT1/2	G1/4	72	52	52	167	53	270.5	
	CFR600-20	70	48	M68×1.5	PT3/4		99	90	66	219	76	363	